

## Sign and Rack Installation Instructions

MSYD (Metal Signs and Your Designs) custom personalized signs and racks add a unique touch to a home or business. The following information will guide you thru the steps to properly install and display your new personalized sign or rack.

### Fastener Type

The fastener type is determined by the surface to which you are attaching your sign or rack. On the interior of a home or business, the most common mounting surface is drywall. Our signs are provided with hardware for this option. For attachment to other surfaces such as wood, stucco, masonry or metal, please visit your local hardware store. The mounting holes are .210 in diameter, which will accommodate a #8 screw. **It is important to purchase the correct hardware type for your application!**

### Mounting Options

Our signs and racks come with thru holes around the perimeter of the sign or rack for direct attachment to the structure of your choice. Our mounting kit comes with #8 stainless steel screws and drywall anchors (quantity depends on size of sign).

### Required Tools

- Drill
- 1/4" Drill Bit (for drywall installation)
- Level
- Phillips Screw Driver
- Pencil
- Additional tools maybe required for mounting surfaces other than drywall



### Installation Instructions

#### 1. Locate, level and mark hole locations

Once you've decided on the perfect spot, mark the location of the mounting holes. Use the sign as a template to mark the location for all mounting holes. Hold the sign against the structure, level the sign, and then use a pencil to mark the hole locations.



## 2. Drill the required hole size based on the hardware requirements

Remove the sign or rack from the surface. The hole locations should be visible after marking. When mounting the sign or rack to drywall, drill a 1/4" hole at the center of the marked hole locations. For other surface types use the appropriate hardware and tools required for attachment.

## 3. Insert the drywall anchors

Insert the drywall anchors into the 1/4" drilled holes. Use a hammer to lightly tap in the drywall anchors. For other surface types, use the manufacturer's instructions.



## 4. Install the sign or rack

Locate the sign or rack holes over the drywall anchor holes. If you selected an optional acrylic colored background, place the acrylic color behind the sign or rack before attaching to the structure. Using the #8 screws, attach the sign or rack to the structure with the screwdriver.

Your installation is finished, enjoy your new personalized product!

